

Item code: 70394-IWN-43IR5

Product description: IP Bullet Camera 4 MP

Main features: IP camera using high performance CMOS image sensor, with 2.0 mega-pixel resolution. Support H.264 and H.265, dual-stream. Max resolution: 2592x1520. Support Onvif, P2P, support ICR switching. PoE, 3 pcs array IR, IR range 25 m, 3.6 mm lens. Metal Bullet casing.



SPECIFICATIONS

Model No.		IWN-43IR5
Sensor		HI3516C V200 1/3" CMOS
Minimum Illumination		Color 0.6 Lux@F1.2, black and white 0.08 Lux@F1.2
Signal to noise ratio		≥50 db (AGC OFF)
WDR		DWDR range 80 db
Code form		H.264 Baseline, Main Profile, High Profile code, MJPEG code
Image output	Main stream	2592x1520, 1-15 fps/2048x1520, 1-25(30)fps (default), 1280x1080, 1-25(30)fps/1280x720, 1-25(30)fps
	Second stream	720x576, 1-25(30)fps/640x480, 1-25(30)fps 640x352, 1-25(30)fps/320x240, 1-25(30)fps
Video compression rate		Support dual stream; support CBR/VBR bit rate, 32 K~16 M bit/S adjustable; frame rate 1-30fps/s adjustable
Network Interface		1 RJ45 Ethernet interface, 10/100 M adaptive;
Network protocol		Supports network protocols such as RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP;
USB interface		A USB interface that can be used for U disk storage or TF storage by adding SD card expansion board. Supports up to 128 G.
TF card storage		Add SD card expansion board to achieve TF storage. Support 128 G maximum.
Automatic aperture		No
Infrared light linkage		Yes
PTZ interface		No
CVBS output		No
3G transmission		No
WiFi transmission		No
PoE power supply		support
Standard agreement		ONVIF
Phone monitoring		Support P2P Support mobile device monitoring iOS Android
Operation Temperature		-10 °C ÷ 55 °C
Camera size (LxWxH)		188×63.5×63.5 mm
Camera weight		320 g