

Item code: 70417-HXVR-16L102H2

Product description: DVR VALUE Series

Main features: TURBO HD DVR 16 Channels: Support H.265 Pro+/H.265 Pro/H.265/ H.264+/H.264 video compression. HDTVI input: 4 MP, AHD input: 4 MP, HDCVI input: 4 MP, CVBS input: PAL/NTSC, Audio IN/Out: 4/1, Serial interface: RS-485 (half-duplex), USB interface: Front panel: 1 Å~ USB 2.0; Rear panel: 1 Å~ USB 3.0, Power supply: 12 Vdc.



SPECIFICATIONS

Recording	
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding resolution	<i>When 1080 p Lite mode is not enabled:</i> 4 MP lite/3 MP/1080 p/720 p/VGA/WD1/4CIF/CIF <i>When 1080 p Lite mode is enabled:</i> 4 MP lite/3 MP/1080 p lite/720 p lite/VGA/WD1/4CIF/CIF
Frame rate	Main stream: <i>When 1080 p Lite mode is not enabled:</i> For 4 MP stream access: 4 MP lite@15 fps; 1080 p lite/720 p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) For 3 MP stream access: 3 MP/1080 p/720 p/VGA/WD1/4CIF/CIF@15 fps For 1080 p stream access: 1080 p/720 p@15 fps; VGA/WD1/4CIF/CIF@25 fps (P)/30 fps (N) For 720 p stream access: 720 p/VGA/WD1/4CIF/CIF@25 fps (P)/30 fps (N) <i>When 1080 p Lite mode enabled:</i> 4 MP lite/3 MP@15 fps; 1080 p lite/720 p lite/VGA/WD1/4CIF/CIF@25 fps (P)/30 fps (N) Sub-stream: WD1/4CIF@12 fps; CIF@25 fps (P)/30 fps (N)
Video bit rate	32 Kbps to 6 Mbps
Dual stream	Support
Stream type	Video, Video & Audio
Audio compression	G.711u
Audio bit rate	64 Kbps
Video and Audio	
IP video input	8-ch (up to 24-ch) Up to 6 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog video input	16-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDTVI input	4 MP, 3 MP, 1080 p 30, 1080 p 25, 720 p 60, 720 p 50, 720 p 30, 720 p 25



BS OHSAS 18001: 2007
Occupational Health and Safety Management System

ISO 14001: 2015
Environmental Management System



ISO 9001: 2015
Quality Management System



CI ITPI: 2015
100% Made in Italy Certificate



MAZi – Brand distributed by LINCE ITALIA S.p.A.
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

	*: The 3 MP signal input is only available for channel 1/2 of DS-7208HQHI-K2, and for channel 1/2/3/4 of DS-7216HQHI-K2
AHD input	4 MP, 1080 p 25, 1080 p 30, 720 p 25, 720 p 30
HDCVI input	4 MP, 1080 p 25, 1080 p 30, 720 p 25, 720 p 30
CVBS input	PAL/NTSC
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
VGA output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
HDMI output	1-ch, 4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Audio output	1-ch, RCA (Linear, 1 KΩ)
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)
Synchronous playback	16-ch
Network	
Remote connection	128
Network protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Network interface	1, RJ45 10M/100M/1000M self-adaptive
Auxiliary Interface	
SATA	2 SATA interfaces
Capacity	Up to 10 TB capacity for each disk
Serial Interface	RS-485 (half-duplex)
USB interface	Front panel: 1 × USB 2.0 Rear panel: 1 × USB 3.0
Alarm in/out	N/A
General	
Power supply	12 Vdc, 5 A
Consumption (without HDD)	≤ 25 W
Working temperature	-10 °C ÷ 55 °C (14 °F ÷ 131 °F)
Working humidity	10% ÷ 90%
Dimension (W × D × H)	380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)
Weight (without HDD)	≤ 2 kg (4.4 lb)