



IWN-42EVR

IP Bullet camera 4MP, 2.8-12 mm lens, 5pcs Array IR, Max 40 M, PoE, 1CH Audio I/O and hardware reset

1/2.9" low-light CMOS sensor

1CH Audio I/O and hardware reset

H.264/H.265/H.265+ video compression standard, dual-stream

Max resolution: 2560*1440

Onvif and P2P

ICR switching

5pcs Array IR, Max 40 M

2.8 -12 mm lens

IP66 metal bullet case

Power supply: PoE/DC12V 500 mA

Camera

Image Sensor 1/2.9, 4MP CMOS GC4653

Min. Illumination Colour 0.01 Lux

Signal to noise ratio ≥ 50 dB

Video

Video processing H.265+/H.265/H.264 video encoding, code stream 0.1M~8Mbps adjustable; frame 1-30fps adjustable

Audio

Audio Port One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom

Network

Network Interface One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection

Protocol Support Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization

Intelligent Functions Humanoid detection
P2P cloud service
Support mobile web access
Support IP filtering

Image

Image Resolution *Main stream:*
30FPS@ (2560 $\times$ 1440, 2304 $\times$ 1296, 1920 $\times$ 1080, 1280 $\times$ 720)
Sub stream:
720 $\times$ 480, D1, VGA, 640 $\times$ 360
Support CBR/VBR

General

Mobile client Support Windows Mobile, iPhone, iPad, Android

Business functions Support IE6.0 and above (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit

Work Environment -30 $\div$ +85 $^{\circ}$ C

Camera Dimension 106.61 x 81.78 mm