



TVN-41EVR

4 MP HD Turret Camera, 2.8-12 mm lens, 3 pcs array IR, IP66

using high performance CMOS image sensor with 4.0 mega-pixel resolution

support coaxial transmission for HD video and control signal

support common 75-5 similar coaxial cables lossless transmission up to 300 m above

high speed, long distance, real-time transmission

support ICR switching

default output is TVI, can switching to AHD/CVI/CVBS by cable

P66 metal dome

3 pcs Array IR, 30 m IR Distance

2.8-12 mm lens

Camera

Sensor	1/2.5; K17
DSP	FH8538E
Active Pixel	2560 x 1944
Sync.	Internal
Minimum Illumination	0.05 Lux @(F1.2)
Resolution	4 MP
Signal to noise ratio	48 dB min (AGC closed)
Transmission distance	75-5 300 m

Video

Video out	TVI: 8 M @15/12.5 fps, 5 M @20/12 fps, 4 M @25/30 fps, 4 M @15 fps, 1080P @25/30 fps AHD: 8 M @15 fps, 5 M @20/12 fps, 4 M @25/30 fps, 4 M @15 fps, 1080P @25/30 fps CVI: 8 M @15/12.5 fps, 5 M @20 fps, 4 M @25/30 fps, 1080P @25/30 fps CVBS: PAL/NTSC
-----------	---

Network

AE	GLOBE/BLC
WB	ATW/MWB
DNR	1-10
D-WDR	Off/On
Mirror	Off/On
OSD	Yes
Language	Eng, Chin1, Chin2, Pycc, Espanol, Francais, Polski, Japanese, Korean, Italiano, Portuges
Day/Night	Auto, Colour, B/W, Ext

General

Power Supply	12 Vdc, 450 mA
Operation Temperature	-10 °C ÷ +55 °C; Humidity less than 85% RH
Dimension (D x H)	145 x 107.86 mm